



HOW TO ORDER:

B 0 7 1 - 1 0 0 2 - 0 1 X - Z

TYPE NUMBER
1 - TYPE 1

PITCH:
0 - 2.54mm
1 - 2.00mm
2 - 1.27mm

COLOR:
1 - BLACK

RoHS COMPLIANT

CONTACT PLATING:
0 - TIN PLATED
1 - GOLD
2 - 3u" GOLD
3 - 10u" GOLD
4 - 15u" GOLD
5 - 30u" GOLD

ELECTRICAL:

CURRENT RATING: 2A
CONTACT RESISTANCE: 30mW Max.
INSULATOR RESISTANCE: 1000MW Min.
DIELECTRIC WITHSTANDING VOLTAGE: 650V rms.

MATERIAL:

CONTACT: PHOSPHOR BRONZE
HOUSING: 30% GLASS FILLED P.B.T. (UL 94V-0)

Rev	Drawn	Checked	Approved	Date
0	A.M.	S.M.	S.M.	09/16/03
A	WHS	S.M.	S.M.	06/08/06

SMP TECHNOLOGY, INC.

1.27mm Shunt, Closed Top, 3.0mm Height

TOL. DEC. .X +/- 0.35 .XX +/- 0.25 .XXX +/- 0.15 ANGLE +/- 2° UNIT: mm

P/N: B071-1002-01X-Z