



HOW TO ORDER:

B **0** **7** **1** - **2** **0** **0** **2** - **0** **1** **X** - **Z**

TYPE NUMBER
 2 - TYPE 2

PITCH:
 0 - 2.54mm
 1 - 2.00mm
 2 - 1.27mm

COLOR:
 1 - BLACK

RoHS COMPLIANT

CONTACT PLATING:
 0 - TIN PLATED
 1 - GOLD
 2 - 3u" GOLD
 3 - 10u" GOLD
 4 - 15u" GOLD
 5 - 30u" GOLD

OF CONTACTS:
 00 - N/A
 02 thru 10

ELECTRICAL:

CURRENT RATING: 2A
 CONTACT RESISTANCE: 30mΩ Max.
 INSULATOR RESISTANCE: 1000MΩ Min.
 DIELECTRIC WITHSTANDING VOLTAGE: 650V rms.

MATERIAL:

CONTACT: PHOSPHOR BRONZE
 HOUSING: NYLON 66+GF (UL94V-0)

Rev	Issued	Apv.	Date
0	Issued	A.M.	09/18/03
A	Revised for RoHS Compliance	WHS	06/08/06

SMP TECHNOLOGY, INC.

SCALE:n/a 1.27mm Shunt, Closed Top w/Handle , 5.5mm Height

TOL. DEC. .X +/- 0.35 .XX +/- 0.25 .XXX +/- 0.15 ANGLE +/- 2° UNIT: mm P/N: B071-2002-01X-Z