



A-A SECTION

HOW TO ORDER:

B 0 7 1 - 2 0 2 2 - 0 1 X - Z

TYPE NUMBER
 2 - TYPE 2

PITCH:
 0 - 2.54mm
 1 - 2.00mm
 2 - 1.27mm

COLOR:
 1 - BLACK

CONTACT PLATING:
 0 - TIN PLATED
 1 - GOLD
 2 - 3u" GOLD
 3 - 10u" GOLD
 4 - 15u" GOLD
 5 - 30u" GOLD

RoHS COMPLIANT

OF CONTACTS:
 00 - N/A
 02 thru 10

ELECTRICAL:

CURRENT RATING: 2A
 CONTACT RESISTANCE: 30mΩ Max.
 INSULATOR RESISTANCE: 1000MΩ Min.
 DIELECTRIC WITHSTANDING VOLTAGE: 650V rms.

MATERIAL:

CONTACT: PHOSPHOR BRONZE
 HOUSING: NYLON 66+GF (UL94V-0)

Rev	Drawn	Checked	Approved	Date
0	A.M.	S.M.	S.M.	09/18/03
A	B.S.	S.M.	S.M.	12/15/06

SMP TECHNOLOGY, INC.

SCALE:n/a 1.27mm Shunt, Closed Top w/Handle , 5.5mm Height, 2 Position