



ELECTRICAL:

VOLTAGE: 40 VAC (RMS) Max.
 CURRENT RATING: 0.5 Amp Per Contact
 CONTACT RESISTANCE: 30 milliohms Max.
 INSULATOR RESISTANCE: 100 Megohms Min.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 DC (RMS)
 OPERATING VOLTAGE: 40 VAC Max.

MATERIAL:

INSULATOR: Black LCP (UL94V-0)
 CONTACT: Copper Alloy
 SHIELD: Stainless Steel
 TERMINAL: Select Au Plating in Contact Area; 100u" Tin Solder Tail;
 All Over 30u" min Nickel Subplate

HOW TO ORDER:

D D 1 0 - 0 0 0 0 - 0 0 X - Z

BOTTOM CONNECTOR:

1 - 20 Position Female DisplayPort

RoHS COMPLIANT

SELECTIVE CONTACT PLATING:

0 - Au Flash / Tin PC Tail
 1 - 15u" Au / Tin PC Tail
 2 - 30u" Au / Tin PC Tail

Rev	Drawn	Checked	Approved	Date
0 Issued	B.S.	S.M.	S.M.	07/06/17

SMP TECHNOLOGY, INC.

Stacked Dual DisplayPort Connector