



ELECTRICAL:

CURRENT: 100VAC 1A MAX. / 12VDC 2A MAX.
 CONTACT RESISTANCE: 30mΩ Max.
 INSULATOR RESISTANCE: 50MΩ Min. AT 250VDC
 OPERATING TEMPERATURE: -35°C~105°C

MATERIAL:

INSULATOR: THERMOPLASTIC PBT (UL94V-0)
 CONTACT: PHOSPHOR BRONZE
 SHIELD: COPPER ALLOY

MECHANICAL:

INSERTION FORCE: 4.5Kg Max.
 WITHDRAWAL FORCE: 0.9~3Kg

HOW TO ORDER:

D **P** **0** **0** - **2** **0** **0** **0** - **0** **X** **0** **X** - **Z**

0 - Receptacle R/A

OF POSITIONS:
 20 - 20 Positions

0 - Thru Hole
 PC Tail

MYLAR OPTION:
 0 - Without Mylar
 1 - With Mylar

SELECTIVE PLATING:
 0 - Au Flash
 1 - 15u" Au
 3 - 30u" Au

RoHS
COMPLIANT

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	06/13/12
A	B.S.	S.M.	S.M.	05/30/19

SMP TECHNOLOGY, INC.

DisplayPort Connector, 20 Position, Right Angle, Thru Hole

TOL. DEC. X. +/- 0.35 X.X +/- 0.25 X.XX +/- 0.15 ANGLE +/- 3° UNIT: mm

P/N: DP00-2000-0X0X-Z