



ELECTRICAL:

CURRENT RATING: 0.5A AC
 CURRENT RATING: 1A DC
 VOLTAGE RATING: 50V AC
 VOLTAGE RATING: 5V DC
 CONTACT RESISTANCE:
 < 20 Milliohm
 INSULATION RESISTANCE:
 > 1000 Megaohm at DC 500V
 DIELECTRIC WITHSTANDING VOLTAGE:
 500V (rms) AC for 1 minute.
 TEMPERATURE RANGE: -25° C to +70° C

MATERIAL:

INSULATOR: ABS 94 HB
 CONTACT PLATING: Sn-Pb Plating
 SCREW TERMINAL: Ni Plating

MECHANICAL:

INSERTION FORCE: 0.3kgf~4kgf
 WITHDRAWAL FORCE: 0.3kgf~4kgf

INSULATOR COLOR CHART

code	pos A	pos B	pos C
1	Red	White	Yellow
2	Red	Green	Blue

HOW TO ORDER

S 9 2 0 - 1 3 0 0 - 0 X 0 - Z

ORIENTATION:

0 - RIGHT ANGLE
 1 - STRAIGHT

MOUNTING OPTION:

0 - w/OUT SCREW MOUNTING HOLES
 1 - w/ SCREW MOUNTING HOLES

SHIELDING OPTION:

0 - NON SHIELDED
 1 - SHIELDED

GROUND SHELL PLATING:

0 - NICKEL
 1 - GOLD

INSULATOR COLOR:

SEE INSULATOR COLOR CHART

RoHS
 COMPLIANT

Rev	Drawn	Checked	Approved	Date
0 Issued	A.M.	S.M.	S.M.	09/02/03
A Revised for RoHS Compliance	B.S.	S.M.	S.M.	07/18/08

SMP TECHNOLOGY, INC.

RCA PIN JACK, 1x3, RIGHT ANGLE, NON-SHIELDED

TOL. DEC. .X +/- 0.35 .XX +/- 0.25 .XXX +/- 0.15 ANGLE +/- UNIT: mm

P/N: S920 - 1300 - 0X0 - Z