



ELECTRICAL:

CURRENT RATING: 7A AC/DC
 VOLTAGE RATING: 250V AC Max.
 CONTACT RESISTANCE: 20 milliohm Max.
 INSULATION RESISTANCE: 1000 Megaohm Min.
 DIELECTRIC WITHSTANDING VOLTAGE:
 1500V (rms) AC for 1 Minute
 OPERATING TEMPERATURE: -25°C to +85°C

MATERIAL:

CONTACT: Phosphor . Bronze, Brass
 APPLICABLE WIRES: AWG# 18 - 22
 FINISH: Tin Plated
 THICKNESS: 0.25mm
 QTY: 4000 pcs./Reel

HOW TO ORDER:

W 0 1 3 - 0 0 2 0 - 0 0 1 - Z

CONTACT PLATING:
1 - TIN PLATED

RoHS COMPLIANT

| Rev | Drawn | Checked | Approved | Date | SMP TECHNOLOGY, INC. | | |
|---|-------------|--------------|----------|-----------|-----------------------------|----------------------------|-------|
| 0 | A.M. | S.M. | S.M. | 01/10/02 | | | |
| A | B.S. | S.M. | S.M. | 08/04/08 | | | |
| | | | | | | | |
| | | | | | | | |
| Contacts For Housing (P/N: W013-XX11-500-Z) | | | | | | | |
| TOL. DEC. | .X +/- 0.35 | .XX +/- 0.25 | .XXX +/- | ANGLE +/- | UNIT: mm | P/N: W013 - 0020 - 001 - Z | Pg: 1 |