



# of Contacts	Dimensions(mm)	
	A	B
2	2.54	5.60
3	5.08	8.14
4	7.62	10.68
5	10.16	13.22
6	12.70	15.76
7	15.24	18.30
8	17.78	20.84
9	20.32	23.38
10	22.86	25.92
11	25.40	28.46
12	27.94	31.00
13	30.48	33.54
14	33.02	36.08
15	35.56	38.62

Housing Accepts Contact P/N: W019-0000-10X-Z

**ELECTRICAL:**

CURRENT RATING: 3A AC, DC  
 VOLTAGE RATING: 250V AC MAX.  
 OPERATING TEMPERATURE: -25 ° TO +85 °C  
 CONTACT RESISTANCE: 20 MILLIOHM MAX.  
 INSULATION RESISTANCE: 1000 MEGAOHM MIN.  
 VOLTAGE WITHSTANDING: 1000V AC / MINUTE

**MATERIAL:**

CONTACT MATERIAL: COPPER ALLOY  
 WAFER MATERIAL: NYLON 6/6 UL 94V-2  
 PACKAGING: 1,000 Pcs/ Bag

**HOW TO ORDER:**

W 0 1 9 - X X 0 4 - 1 2 0 - Z

**NUMBER OF CONTACTS:**  
02THRU15

**RoHS COMPLIANT**

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	5/31/07

**SMP TECHNOLOGY, INC.**

2.54mm Pitch, Housing, Locking Type

SCALE: N/A

TOL. DEC. .X +/- 0.3 .XX +/- 0.2 .XXX +/- 0.1 ANGLE +/- UNIT: mm

SERIES: W019-XX04-120-Z