



# of Contacts	Dimensions(mm)	
	A	B
2	2.00	5.80
3	4.00	7.80
4	6.00	9.80
5	8.00	11.80
6	10.00	13.80
7	12.00	15.80
8	14.00	17.80
9	16.00	19.80
10	18.00	21.80
11	20.00	23.80
12	22.00	25.80
13	24.00	27.80
14	26.00	29.80
15	28.00	31.80
16	30.00	33.80

Accepts Contact P/N: W034-0002-001-Z

ELECTRICAL:
 CURRENT RATING: 2A AC/DC
 VOLTAGE RATING: 100V AC/DC
 CONTACT RESISTANCE: 20 mΩ max.
 WITHSTANDING VOLTAGE: 800V AC for 1 min.
 INSULATION RESISTANCE: 1000 MΩ min.
 TEMPERATURE RANGE: -25°C to 85°C

MATERIAL:
 INSULATOR: Nylon 66 UL94V-0

HOW TO ORDER:

W 0 3 4 - X X 4 1 - 0 0 0 - Z

OF POSITIONS:
 02 - 32 Position

HOUSING & TERMINATION TYPE:
 4 - Housing For Contacts

**RoHS
 COMPLIANT**

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	5/3/07

SMP TECHNOLOGY, INC.

SCALE:n/a

Housing, 2.0mm Pitch, JST PHD Type

TOL. DEC. .X +/- 0.3 .XX +/- 0.2 .XXX +/- 0.1 ANGLE +/- UNIT: mm

P/N:W034-XX41-000-Z