



UNIT:mm

MODEL	OUTPUT AC		
	VOLTAGE(V)	CURRENT(mA)	VA
AD-0901000AU	9	1000	9
AD-0901500AU	9	1500	13.5
AD-1200800AU	12	800	9.6
AD-1200850AU	12	850	10.2
AD-1201000AU	12	1000	12
AD-1201200AU	12	1200	14.4
AD-1201500AU	12	1500	18
AD-1201700AU	12	1700	20.4
AD-1351000AU	13.5	1000	13.5
AD-1500800AU	15	800	12
AD-1501000AU	15	1000	15
AD-1600800AU	16	800	12.8
AD-1601000AU	16	1000	16
AD-1800600AU	18	600	10.8
AD-1801000AU	18	1000	18
AD-2400400AU	24	400	9.6
AD-2400500AU	24	500	12
AD-1002000AU	10	2000	20
AD-1201666AU	12	1666	20
AD-1651200AU	16.5	1200	19.8
AD-1651500AU	16.5	1500	24.75
AD-2400830AU	24	830	19.92

FOR OUTPUT PLUG TABLE
SEE PAGE 2

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	09/05/08

SMP TECHNOLOGY, INC.

AC/AC ADAPTER, WALLMOUNT, PLUG IN CLASS 2 TRANSFORMER,

INPUT: 120VAC 60Hz, SAFETY: UL1310 & 1950 & CUL

STRAIGHT

MALE PLUG STRAIGHT (parallel cord)

	Part Number	D +/-0.1		L+/-0.5	Wire Gauge
	SM1A	ø2.5		11	#22 #24
	SM2A	ø3.5		14	#22 #24

MALE PLUG STRAIGHT (parallel/coaxial cord)

	Part Number	D +/-0.1		L+/-0.5	Wire Gauge
	SM2B	ø3.5		14	#22 #24

FEMALE PLUG STRAIGHT (parallel cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	SF2A	ø3.5	ø1.3	7	#22 #24
	SF2B	ø3.5	ø1.3	9.5	#22 #24
	SF2C	ø3.5	ø1.3	11	#22 #24
	SF2D	ø3.5	ø1.3	14	#22 #24
	SF3A	ø5.0	ø2.1	9.5	#20
	SF3B	ø5.0	ø2.1	11	#20
	SF3C	ø5.0	ø2.1	14	#20
	SF5C	ø5.5	ø2.5	9.5	#18,#20
	SF5B	ø5.5	ø2.5	11	#18,#20
SF5A	ø5.5	ø2.5	14	#18,#20	
SF6A	ø6.5	ø3.0	9.5	#20	
SF6B	ø6.5	ø3.0	11	#20	

FEMALE PLUG STRAIGHT (parallel cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	SF3D	ø5.0	ø2.1	9.5	#22 #24
	SF3E	ø5.5	ø2.1	11	#22 #24
	SF5D	ø5.5	ø2.1	9.5	#22 #24
SF5E	ø5.5	ø2.5	11	#22 #24	

FEMALE PLUG STRAIGHT (parallel cord #20,#22,#24 /Coaxial #22)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	SF5F	ø5.5	ø2.1	9.5	#20,#22,#23
	SF5G	ø5.5	ø2.1	11	#20,#22,#23
	SF5H	ø5.5	ø2.5	9.5	#20,#22,#23
SF5I	ø5.5	ø2.5	11	#20,#22,#23	

FEMALE PLUG STRAIGHT (SPT-1#18 & XTW-A #20 Cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
SF5J	ø5.5	ø2.1	12.5	#18,#20	

FEMALE PLUG STRAIGHT (parallel/coaxial cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	SF5K	ø5.5	ø2.1	9.5	#22 #24
	SF5L	ø5.5	ø2.1	11	#22 #24
	SF5M	ø5.5	ø2.1	14	#22 #24
SF5N	ø5.5	ø2.5	11	#22 #24	

MINI DIN MALE PLUG, STRAIGHT

	Part Number	Pin Configuration
	SMD3	
	SMD4	
	SMD5	
	SMS5	
	SMD6	
	SMD7	

RIGHT ANGLE

FEMALE PLUG RIGHT ANGLE (parallel cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	RF4A	ø5.03	ø1.57	8.2	#22 #24
	RF4B	ø5.03	ø1.57	13.5	#22 #24
	RF3A	ø5.0	ø2.1	9	#22 #24
	RF3B	ø5.0	ø2.1	11	#22 #24
	RF3C	ø5.0	ø2.5	11	#22 #24
	RF5A	ø5.5	ø1.3	11	#22 #24
	RF5B	ø5.5	ø2.1	9.5	#22 #24
	RF5C	ø5.5	ø2.5	9.5	#22 #24
	RF5D	ø5.5	ø2.1	11	#22 #24
RF5E	ø5.5	ø2.5	11	#22 #24	

FEMALE PLUG RIGHT ANGLE (parallel cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	RF2A	ø3.5	ø1.3	9	#22 #24
	RF2B	ø3.5	ø1.3	11	#22 #24
	RF5F	ø5.5	ø2.1	9.5	#22 #24
	RF5G	ø5.5	ø2.1	11	#22 #24
	RF5H	ø5.5	ø2.5	9.5	#22 #24
RF5I	ø5.5	ø2.5	11	#22 #24	

FEMALE PLUG RIGHT ANGLE (Coaxial cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	RF5J	ø5.5	ø2.1	9.5	#22 #24
	RF5K	ø5.5	ø2.1	11	#22 #24
	RF5L	ø5.5	ø2.5	9.5	#22 #24
RF5M	ø5.5	ø2.5	11	#22 #24	

MALE/FEMALE PLUG RIGHT ANGLE (Parallel cord)

	Part Number	D +/-0.1		L+/-0.5	Wire Gauge
RM2A	ø3.5		16.5	#22 #24	

MINI DIN MALE PLUG, RIGHT ANGLE

	Part Number	Pin Configuration
	RMD3	
	RMD4	
	RMD5	
	RMS5	
	RMD6	
	RMD7	

OUTPUT PLUG TABLE